



RADE KONČAR KONTAKTORI I RELEI D.O.O.



| Nazivna nominalna struja Ie kod Un=400 V, AC 1 | Nazivna nominalna snaga Pn, Un=400 V, AC 3 | Broj pomoćnih kontakata 1 0 1 1 | Dimenzije a x b x c | Težina | MOTORNI KONTAKTORI, naizmenični napon upravljanja | Cena |
|--|--|---------------------------------------|---------------------|--------|---|------------|
| (A) | (kW) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 20 | 3,0 | 1 0 0 1 | 45x48x57 | 0,17 | CM1 10 | 1361 |
| 25 | 4,5 | 0 0 | 45x71x72,2 | 0,25 | CNN 9 00 | 1420 |
| | | 1 0 0 1 | | | CNN 9 10 | 1455 |
| 25 | 4,5 | 0 0 | 45x71x72,2 | 0,25 | CNN 9 004 ; CNN 9 00 22 | 1545 |
| 25 | 5,7 | 0 0 | 45x71x72,2 | 0,25 | CNN 12 00 | 1556 |
| | | 1 0 0 1 | | | CNN 12 10 | 1620 |
| 25 | 5,7 | 0 0 | 45x71x72,2 | 0,25 | CNN 12 004 ; CNN 12 00 22 | 1730 |
| 30 | 7,5 | 1 0 | 45x71x72,2 | 0,26 | CNN 18 10 | 1925 |
| | | 0 1 | | | | |
| 40 | 11 | 0 0 | 45x71x72,2 | 0,275 | CNN 25 00 | 2500 |
| 40 | 15 | 0 0 | 45x71x72,2 | 0,290 | CNN 30 00 | 2958 |
| 50 | 15 | 0 0 | 45x80x84,6 | 0,355 | CNN 32 00 | 3560 |
| 50 | 18,5 | 0 0 | 45x80x84,6 | 0,355 | CNN 40 00 | 4356 |
| 80 | 22 | 0 0 | 55x120x109 | 0,845 | CNN 50 00 | 6185 |
| 85 | 30 | 0 0 | 55x120x109 | 0,850 | CNN 60 00 | 7825 |
| 85 | 33 | 0 0 | 70x142x123 | 0,900 | CNN 70 00 | 9188 |
| 90 | 37 | 0 0 | 70x142x123 | 1,280 | CNN 80 00 | 11486 |
| 95 | 45 | 0 0 | 70x142x123 | 1,300 | CNN 90 00 | 12985 |
| 100 | 55 | 0 0 | 70x142x123 | 1,350 | CNN 100 00 | 13900 |
| | | 1 0 1 1 | | | Dodaci (blokovi pomoćnih kontakata) | RSD |
| | | 0 1 | 45x48x38 | 0,04 | BPO (40, 31, 22, 13, 04), prednji | 750 |
| | | 3 1 | | | | |
| | | 2 2 | | | | |
| | | 1 3 | | | | |
| | | 0 4 | | | | |
| | | 1 0 0 1 | | 0,013 | BP1 (1NO ili 1NC), stranični | 320 |
| | | 1 1 | 40x35x38 | 0,03 | BP2 11 (1NO+1NC), prednji | 384 |
| | | 1 1 | 55x10x46 | 0,05 | BP5 11 (1NO+1NC), stranični | 650 |
| | | 1 1 | 55x10x46 | 0,03 | BP3 11 (1NO+1NC), stranični | 353 |
| | | 2 2 | 40x35x38 | 0,04 | BP4 22 (2NO+2NC), prednji | 461 |
| | | 4 0 | 40x35x38 | 0,04 | * BP4 40 (4NO+0NC), prednji | 461 |
| | | 2 2 | 40x35x38 | 0,04 | BP2 N 11 (1NO+1NC), prednji | 650 |
| | | 2 2 | 40x35x38 | 0,04 | BP4 N 22 (2NO+2NC), prednji | 808 |



| Nazivna nominalna struja Ie kod Un=400 V, AC 1 | Nazivna nominalna snaga Pn, Un=400 V, AC 3 | Broj pomoćnih kontakata Y Z | Dimenzije a x b x c | Težina | MOTORNI KONTAKTORI, naizmenični napon upravljanja | Cena |
|--|--|--------------------------------|--|--------|---|--------|
| (A) | (kW) | ukl/iskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 63 | 22 | 2 2 | 87x114x111 | 1,30 | CNM 45 22 | 7405 |
| | | 4 4 | 112x114x111 | 1,40 | CNM 45 44 | 8805 |
| 72 | 30 | 2 2 | 87x114x111 | 1,30 | CNM 60 22 | 8918 |
| | | 4 4 | 112x114x111 | 1,40 | CNM 60 44 | 10314 |
| 100 | 37 | 2 2 | 100x132x142 | 2,27 | CNM 75 22 | 13503 |
| | | 4 4 | 125x132x142 | 2,37 | CNM 75 44 | 14818 |
| 110 | 45 | 2 2 | 100x132x142 | 2,28 | CNM 90 22 | 16695 |
| | | 4 4 | 125x132x142 | 2,38 | CNM 90 44 | 18158 |
| 115 | 55 | 2 2 | 100x132x142 | 2,29 | CNM 110 22 | 17921 |
| | | 4 4 | 125x132x142 | 2,39 | CNM 110 44 | 19351 |
| | | 2 2 | 135x180x189 | 5,10 | CNM 140 22 | 27178 |
| | | 4 4 | 135x180x189 | 5,60 | CNM 140 44 | 29153 |
| | | 2 2 | 135x180x189 | 5,20 | CNM 170 22 | 30582 |
| | | 4 4 | 162x180x189 | 5,70 | CNM 170 44 | 32889 |
| | | 2 2 | 135x180x189 | 5,30 | CNM 200 22 | 37209 |
| | | 4 4 | 162x180x189 | 5,80 | CNM 200 44 | 39566 |
| | | 2 2 | 160x200x226 | 8,40 | CNM 250 22 | 50412 |
| | | 4 4 | 187x200x226 | 8,90 | CNM 250 44 | 52907 |
| | | 2 2 | 160x200x226 | 8,50 | CNM 315 22 | 62810 |
| | | 4 4 | 187x200x226 | 8,90 | CNM 315 44 | 64765 |
| | | 2 2 | 160x200x226 | 8,50 | CNM 400 22 | 75945 |
| | | 4 4 | 187x200x226 | 8,90 | CNM 400 44 | 77920 |
| 700 | 250 | 2 2 | 220x250x225 | 13,50 | CNM 450 22 | 128125 |
| 800 | 315 | 2 2 | 220x250x225 | 14,00 | CNM 550 22 | 164897 |
| 1000 | 400 | 2 2 | 280x307x291 | 26,40 | CNM 700 22 | 182148 |
| 1100 | 500 | 2 2 | 280x307x291 | 27,80 | CNM 860 22 | 254969 |
| 1200 | 580 | 2 2 | 334x490x345 | 51,00 | CNM 1000 22 | 705769 |
| | | Težina(kg) | Dodatci | | | |
| | | | RC elementi za CNNP ; CNN9 - CNN 40 | | | 359 |
| | | 0,021 | dodatci za priključke za (CNN 32 - CNN 40) za priključenje vodiča do 25mm ² , (2 komada),br.dela:601478 | | | 769 |
| | | 0,14 | Set od 6 štitnika (poklopca) za terminale kontaktora (CNM 75-CNM110),br.dela:603311 | | | 2563 |
| | | 0,15 | Set od 6 štitnika (poklopca) za terminale kontaktora (CNM 140-CNM200),br.dela:604128 | | | 3075 |
| Nazivna nominalna struja Ie kod Un=400 V, AC 1 | Nazivna nominalna snaga Pn, Un=400 V, AC 3 | Broj pomoćnih kontakata Y Z | Dimenzije a x b x c | Težina | MOTORNI KONTAKTORI, naizmenični napon upravljanja | Cena |
| (A) | (kW) | ukl/iskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 23 | 4,7 | 1 1 | 68x68x78,5 | 0,425 | CN 10 | 3167 |
| | | 2 0 | | | | |
| | | 0 2 | | | | |
| 30 | 7,5 | 1 1 | 68x68x78,5 | 0,425 | CN 16 | 3361 |
| | | 2 0 | | | | |
| | | 0 2 | | | | |
| 35 | 12 | 2 2 | 85x100x103 | 0,930 | CN 25 | 7386 |
| 45 | 15 | 2 2 | 85x100x103 | 0,935 | CN 40 | 9253 |
| 130 | 40 | 2 2 | 192x190x130 | 5,50 | CN 80 | 26950 |
| 160 | 55 | 2 2 | 192x190x130 | 5,60 | CN 110 | 32235 |
| 220 | 90 | 2 2 | 212x234x180 | 9,50 | CN 170 | 58110 |
| 300 | 132 | 2 2 | 212x234x180 | 9,70 | CN 250 | 82000 |



| Nazivna nominalna struja Ie kod Un=230 V, AC 15/AC 14 | | Broj pomoćnih kontakata ↘ ↗ | Dimenzije a x b x c | Težina | MOTORNI KONTAKTORI, naizmjenični napon upravljanja | Cena |
|---|--|---------------------------------|---------------------|--------|--|-------|
| (A) | | ukl/fiskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 6 | | 4 0 3 1 2 2 | 45x48x56 | 0,17 | CP0 | 1359 |
| 10 | | 4 0 3 1 2 2 1 3 0 4 | 45x71x72,2 | 0,25 | CNNP | 1466 |
| | | sve izvedbe kao CNNP | 45x71x72,2 | 0,27 | CNNP F | 1974 |
| Nazivna nominalna struja Ie kod Un=400 V, AC 6b | Snaga kondenz. kod Un=400V, AC 6b | Broj pomoćnih kontakata ↘ ↗ | Dimenzije a x b x c | Težina | Kondenzatorski kontaktori CNNK naizmjenični napon upravljanja | Cena |
| (A) | (kVar) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 18 | 2,5 | 1 0 | 45x71x72,2 | 0,25 | CNNK 2,5 | 1800 |
| 18 | 5 | 1 0 | 45x71x72,2 | 0,25 | CNNK 5 | 2010 |
| 29 | 7,5 | 0 0 | 45x71x72,2 | 0,275 | CNNK 7,5 | 2193 |
| 14 | 10 | 2 0 | 45x72,2x108 | 0,314 | CNNK 10 20 | 2385 |
| 14 | 10 | 1 1 | 45x72,2x108 | 0,314 | CNNK 10 11 | 2385 |
| 18 | 12,5 | 2 0 | 45x72,2x108 | 0,316 | CNNK 12 20 | 2519 |
| 18 | 12,5 | 1 1 | 45x72,2x108 | 0,316 | CNNK 12 11 | 2519 |
| 22 | 15 | 2 0 | 45x72,2x108 | 0,318 | CNNK 15 20 | 2981 |
| 22 | 15 | 1 1 | 45x72,2x108 | 0,318 | CNNK 15 11 | 2981 |
| 29 | 20 | 1 0 | 45x80x121,3 | 0,333 | CNNK 20 10 | 3208 |
| 36 | 25 | 1 0 | 45x80x121,3 | 0,404 | CNNK 25 E 10 | 4044 |
| 36 | 25 | 1 0 | 45x80x121,4 | 0,404 | CNNK 25 10 | 4408 |
| 44 | 30 | 1 0 | 45x80x121,3 | 0,414 | CNNK 30 10 | 5028 |
| 50 | 40 | 1 0 | 55x120x109 | 0,875 | CNNK 40 10 | 6530 |
| 72 | 50 | 1 0 | 55x120x109 | 0,880 | CNNK 50 10 | 7434 |
| 87 | 60 | 1 0 | 55x120x109 | 0,920 | CNNK 60 10 | 8619 |
| 101 | 70 | 1 0 | 70x142x123 | 1,320 | CNNK 70 10 | 13100 |
| 108 | 75 | 2 2 | 130x158x145 | 2 | CNKM 75 22 | 15619 |
| 108 | 75 | 2 2 | 130x158x145 | 2,47 | CNKM 80 22 | 19200 |
| Nazivna nominalna struja Ie kod Un=400 V, AC 1 | Nazivna nominalna snaga Pn, Un=400 V, AC 1 | Broj pomoćnih kontakata ↘ ↗ | Dimenzije a x b x c | Težina | TERMIČKI KONTAKTORI, naizmjenični napon upravljanja | Cena |
| (A) | (kW) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 65 | 43 | 2 2 | 45x129x113 | 0,59 | TKN 65 00 | 6174 |
| 115 | 76 | 2 2 | 87x172x111 | 1,50 | TKN 115 22 | 10857 |
| 130 | 85 | 2 2 | 100x158x140 | 2,42 | TK 130 22 | 18891 |
| 175 | 115 | 2 2 | 100x158x140 | 2,42 | TK 175 22 | 20852 |



| Nazivna nominalna struja Ie kod Un=400 V, AC 2/AC3 | Nazivna nominalna snaga Pn, Un=400 V, AC 2/AC3 | Broj pomoćnih kontakata Y T | Dimenzije a x b x c | Težina | Kontaktori MBCNN i MBCNM (mehanička i električna blokada) | Cena |
|--|--|--------------------------------|---------------------|--------|---|--------|
| (A) | (kW) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 6,5 | 2,2 | 0 0 | 83x110x56 | 0,41 | MBCM1 00 | 3951 |
| 6,5 | 2,2 | 1 0 | 83x110x56 | 0,41 | MBCM1 10 | 4273 |
| 9 | 4,5 | 0 0 | 100x72,2x71 | 0,503 | MBCNN 9 00 | 4434 |
| 9 | 4,5 | 1 1 | 120x72,2x71 | 0,505 | MBCNN 9 11 | 5106 |
| 12 | 5,7 | 0 0 | 100x72,2x71 | 0,503 | MBCNN 12 00 | 4918 |
| 12 | 5,7 | 1 1 | 120x72,2x71 | 0,505 | MBCNN 12 11 | 5590 |
| 18 | 7,5 | 0 0 | 100x72,2x71 | 0,523 | MBCNN 18 00 | 5563 |
| 18 | 7,5 | 1 1 | 120x72,2x71 | 0,525 | MBCNN 18 11 | 6235 |
| 25 | 11 | 1 0 | 100x72,2x71 | 0,553 | MBCNN 25 10 | 7538 |
| 30 | 11 | 1 0 | 100x72,2x71 | 0,553 | MBCNN 30 10 | 8425 |
| 32 | 15 | 1 0 | 120x80x84,6 | 0,713 | MBCNN 32 10 | 10078 |
| 40 | 18,5 | 1 0 | 120x80x84,6 | 0,713 | MBCNN 40 10 | 11933 |
| 45 | 22 | 1 0 | 160x140x111 | 2,80 | MBCNN 50 10 | 18060 |
| 45 | 22 | 2 1 | 160x140x111 | 2,80 | MBCNN 50 21 | 19404 |
| 60 | 30 | 1 0 | 160x140x111 | 2,82 | MBCNN 60 10 | 22575 |
| 60 | 30 | 2 1 | 160x140x111 | 2,82 | MBCNN 60 21 | 23919 |
| 65 | 33 | 1 0 | 160x140x111 | 2,88 | MBCNN 70 10 | 28219 |
| 65 | 33 | 2 1 | 160x140x111 | 2,88 | MBCNN 70 21 | 29563 |
| 75 | 37 | 1 0 | 200x150x102 | 3,78 | MBCNN 80 10 | 34266 |
| 75 | 37 | 2 1 | 200x150x102 | 3,78 | MBCNN 80 21 | 35609 |
| 90 | 45 | 1 0 | 200x150x102 | 3,81 | MBCNN 90 10 | 36684 |
| 90 | 45 | 2 1 | 200x150x102 | 3,81 | MBCNN 90 21 | 38028 |
| 110 | 55 | 2 1 | 200x150x102 | 5,78 | MBCNM 110 21 | 52003 |
| 140 | 75 | 2 1 | 270x210x189 | 14,20 | MBCNM 140 21 | 80222 |
| 170 | 90 | 2 1 | 270x210x189 | 14,40 | MBCNM 170 21 | 92719 |
| 200 | 105 | 2 1 | 270x210x189 | 14,60 | MBCNM 200 21 | 108844 |
| 250 | 132 | 2 1 | 310x235x226 | 23,00 | MBCNM 250 21 | 149156 |
| 315 | 160 | 2 1 | 310x235x226 | 23,20 | MBCNM 315 21 | 181406 |
| 400 | 200 | 2 1 | 310x235x226 | 23,40 | MBCNM 400 21 | 225750 |
| Dodatci | | | | | | |
| | | | | 0,003 | MB2, mehanička blokada za CNN9-CNN4 | 954 |
| | | | | | MB3, mehanička blokada za CNN50-CNN | 4166 |
| Nazivna nominalna struja Ie kod Un=400 V, AC 1 | Nazivna nominalna snaga Pn, Un=400 V, AC 3 | Broj pomoćnih kontakata Y T | Dimenzije a x b x c | Težina | Bešumni kontaktori CNB jednosmerni napon upravljanja | Cena |
| (A) | (kW) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 24, 110, 220 DC | RSD |
| 10 | 4,5 | 4 0 | 45x90x129 | 0,60 | CNB | 2661 |
| | | 3 1 | | | | |
| | | 2 2 | | | | |
| | | 1 3 | | | | |
| | | 0 4 | | | | |
| | | | | | CNNPB F | 3043 |
| 25 | 4,5 | 1 0 | | | CNNB 9 10 | 2661 |
| 25 | 5,7 | 1 0 | | | CNNB 12 10 | 2914 |
| 30 | 7,5 | 3 2 | | | CNNB 18 10 | 3303 |
| 40 | 11 | 0 0 | | | CNNB 25 00 | 3515 |
| | | 2 2 | | | CNNB 30 00 | 4107 |



| Nazivna nominalna struja le kod Un=400 V, AC 1 | Nazivna nominalna snaga Pn, Un=400 V, AC 3 | Broj pomoćnih kontakata ↓ ↓ | Dimenzije a x b x c | Težina | MOTORNI KONTAKTORI jednosmerni napon upravljanja | Cena |
|---|---|--------------------------------|---------------------|--------|--|--------|
| (A) | (kW) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 24, 110, 220 DC | RSD |
| 16 | | 4 0 | 45x75x85 | 0,37 | CNNP 40 EG | 2822 |
| 25 | 4,5 | 1 0 | 50x71x72,2 | 0,25 | CNN 9 10 | 2016 |
| 25 | 5,7 | 1 0 | 50x71x72,2 | 0,25 | CNN 12 10 | 2177 |
| 30 | 7,5 | 1 0 | 50x71x72,2 | 0,26 | CNN 18 10 | 2392 |
| 40 | 11 | 1 0 | 50x71x72,2 | 0,275 | CNN 25 10 | 3118 |
| 40 | 15 | 1 0 | 50x71x72,2 | 0,290 | CNN 30 10 | 3413 |
| 50 | 15 | 1 0 | 50x80x84,6 | 0,36 | CNN 32 10 | 3964 |
| 50 | 18,5 | 1 0 | 50x80x84,6 | 0,36 | CNN 40 10 | 4821 |
| 85 | 22 | 1 0 | 60x120x109 | 0,85 | CNN 50 10 | 6692 |
| 85 | 30 | 1 0 | 60x120x109 | 0,85 | CNN 60 10 | 8197 |
| 90 | 33 | 1 0 | 75x142x123 | 0,90 | CNN 70 10 | 10078 |
| 95 | 37 | 1 0 | 75x142x123 | 1,28 | CNN 80 10 | 13077 |
| 105 | 45 | 1 0 | 75x142x123 | 1,30 | CNN 90 10 | 14883 |
| 105 | 50 | 1 0 | 75x142x123 | 1,350 | CNN 100 10 | 15856 |
| 115 | 55 | 2 1 | 100x132x142 | 2,29 | CNM 110 21 (11) | 19350 |
| | | 4 3 | 125x132x142 | 2,39 | CNM 110 43 (33) | 20963 |
| 250 | 75 | 2 1 | 135x180x189 | 5,10 | CNM 140 21 (12) | 28084 |
| | | 4 3 | 162x180x189 | 5,60 | CNM 140 43 (34) | 30208 |
| 250 | 90 | 2 1 | 135x180x189 | 5,20 | CNM 170 21 (12) | 32250 |
| | | 4 3 | 162x180x189 | 5,70 | CNM 170 43 (34) | 34938 |
| 250 | 105 | 2 1 | 135x180x189 | 5,30 | CNM 200 21 (12) | 37625 |
| | | 4 3 | 162x180x189 | 5,80 | CNM 200 43 (34) | 40313 |
| 350 | 132 | 2 1 | 160x200x226 | 8,40 | CNM 250 21 (12) | 52406 |
| | | 4 3 | 187x200x226 | 8,90 | CNM 250 43 (34) | 55094 |
| 390 | 160 | 2 1 | 160x200x226 | 8,50 | CNM 315 21 (12) | 63156 |
| | | 4 3 | 187x200x226 | 8,90 | CNM 315 43 (34) | 65844 |
| 450 | 200 | 2 1 | 160x200x226 | 8,50 | CNM 400 21 (12) | 77938 |
| | | 4 3 | 187x200x226 | 8,90 | CNM 400 43 (34) | 80625 |
| 23 | 4,7 | 11 02 20 | 68x68x78,5 | 0,425 | CN 10 | 4112 |
| 30 | 7,5 | 11 02 20 | 68x68x78,5 | 0,425 | CN 16 | 4367 |
| 35 | 12 | 2 2 | 85x100x103 | 0,930 | CN 25 | 9594 |
| 45 | 15 | 2 2 | 85x100x103 | 0,935 | CN 40 | 12013 |
| 130 | 40 | 2 2 | 192x190x130 | 5,50 | CN 80 | 31686 |
| 160 | 55 | 2 2 | 192x190x130 | 5,60 | CN 110 | 38404 |
| 220 | 90 | 2 2 | 212x234x180 | 9,50 | CN 170 | 68531 |
| 300 | 132 | 2 2 | 212x234x180 | 9,70 | CN 250 | 98766 |
| Nazivna nominalna struja le kod Un=220 V, DC3/DC5 | Nazivna nominalna snaga Pn, Un=220 V, DC3/DC5 | Broj pomoćnih kontakata ↓ ↓ | Dimenzije a x b x c | Težina | KONTAKTORI za DC MOTORE jednosmerni napon upravljanja | Cena |
| (A) | (kW) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 24, 110, 220 DC | RSD |
| 30 | 5 | 2 2 | 85x100x103 | 0,97 | CNO 30 22 | 9689 |
| 30 | 5 | 2 2 | 85x100x103 | 0,97 | CNOg 30 22 | 10176 |
| 80 | 16 | 2 2 | 192x190x130 | 5,70 | CNO 110 22 | 42115 |
| 170 | 22 | 2 2 | 212x234x180 | 9,70 | CNO 250 22 | 107599 |
| | | | | Težina | KONTAKTORI za DC MOTORE jednosmerni napon upravljanja | Cena |
| (A) | (kW) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 30 | 5 | 2 2 | 85x100x103 | 0,97 | CNO 30 22 | 9202 |
| 30 | 5 | 2 2 | 85x100x103 | 0,97 | CNOg 30 22 | 9666 |
| 80 | 16 | 2 2 | 192x190x130 | 5,70 | CNO 110 22 | 36467 |
| 170 | 22 | 2 2 | 212x234x180 | 9,70 | CNO 250 22 | 93165 |
| | | | | | SKLOPNICI U KUĆISTU naizmjenični napon upravljanja | Cena |
| (A) | (kW) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 25 | 4 | 1 0 | 100x191x123 | | PN 9 | 3288 |
| 25 | 5,5 | 2 2 | 100x191x123 | | PN 12 | 3834 |
| 25 | 7,5 | 2 2 | 100x191x123 | | PN 16 | 4446 |
| 35 | 11 | 2 2 | 100x191x123 | | PN 22 | 5312 |
| 39 | 15 | 2 2 | 100x191x123 | | PN 30 | 6652 |

| Nazivna nominalna struja Ie kod Un=400 V, AC 1 | Nazivna nominalna snaga Pn, Un=400 V, AC2/AC3 | Broj pomoćnih kontakata y z | Dimenzije a x b x c | Težina | SKLOPNICI sa BIMETALNIM RELEJEM U KUĆIŠTU naizmenični napon upravljanja | Cena |
|--|---|--------------------------------|---------------------|--------|---|-------|
| (A) | (kW) | ukl/fiskl | (mm) | (kg) | Standardni naponi: 230V/50Hz; 400V/50Hz | RSD |
| 25 | 4 | | 100x191x123 | | PNRT 9 | 6762 |
| 25 | 5,5 | 1 2 | 100x191x123 | | PNRT 12 | 7395 |
| 25 | 7,5 | 1 2 | 100x191x123 | | PNRT 16 | 8010 |
| 35 | 11 | 1 2 | 100x191x123 | | PNRT 22 | 9397 |
| 39 | 15 | 1 2 | 100x191x123 | | PNRT 30 | 10737 |
| 25 | 4 | 1 0 | 100x191x123 | | PNRG 9 | 6368 |
| 25 | 5,5 | 2 2 | 100x191x123 | | PNRG 12 | 7001 |
| 25 | 7,5 | 2 2 | 100x191x123 | | PNRG 16 | 7613 |
| 35 | 11 | 2 2 | 100x191x123 | | PNRG 22 | 9000 |
| 39 | 15 | 2 2 | 100x191x123 | | PNRG 30 | 10342 |

REZERVNI DELOVI ZA KONTAKTORE

Cena (RSD)

| Tip | Glavni kontakti komplet | Jedan blok pomoćnih kontakata | KALEM naizmenični napon upravljanja | KALEM jednosmerni napon | Lučna komora |
|----------------------|-------------------------|-------------------------------|-------------------------------------|-------------------------|--------------|
| CNM 36 | 2537 | 641 | 1009 | 1110 | |
| CNM 45 | 3049 | 641 | 2199 | 2419 | |
| CNM 60 | 4818 | 641 | 2199 | 2419 | |
| CNM 75 | 6944 | 641 | 3881 | 4269 | 2858 |
| CNM 90 | 8431 | 641 | 3881 | 4269 | 2858 |
| CNM 110 | 9328 | 641 | 3881 | 4269 | 2858 |
| CNM 140 | 12172 | 1025 | 6443 | 7090 | 7303 |
| CNM 170 | 13607 | 1025 | 6443 | 7090 | 7303 |
| CNM 200 | 18886 | 1025 | 6443 | 7090 | 7303 |
| CNM 250 | 25266 | 1025 | 12420 | 13662 | 14658 |
| CNM 315 | 35142 | 1025 | 12420 | 13662 | 14658 |
| CNM 400 | 41846 | 1025 | 12420 | 13662 | 14658 |
| CN 10 | 1271 | 999 | 1268 | 1395 | |
| CN 16 | 1348 | 999 | 1268 | 1395 | |
| CN 25 | 2281 | 1614 | 2536 | 2789 | 1361 |
| CN 40 | 2783 | 1614 | 2536 | 2789 | 1547 |
| CNO 30 | 3062 | 1614 | 2536 | 2789 | 2343 |
| CN 63 | 5927 | 2588 | 4899 | 5387 | 2170 |
| CNO 63 | 6519 | 2588 | 4899 | 5387 | 2170 |
| CN 80 | 8764 | 2588 | 6968 | 7664 | 3407 |
| CN 110 | 10609 | 2588 | 6968 | 7664 | 4333 |
| CNO 110 | 11670 | 2588 | 6968 | 7664 | 4333 |
| CN 170 | 19027 | 2588 | 13455 | 14801 | 9907 |
| CN 250 | 27291 | 2588 | 13455 | 14801 | 9907 |
| CNO 250 | 30020 | 2588 | 13455 | 14801 | 9907 |
| CNB 50 | 6381 | 2588 | | 6888 | 2170 |
| TK 115 | 5791 | 1256 | 2199 | | |
| TK 130 | 8328 | 1256 | 3881 | | 2857 |
| TK 175 | 11198 | 1256 | 3881 | | 2857 |
| CM1 | | | 1000 | | |
| CNP 21/31 | | | 1000 | | |
| CNM 9,12,16,22,30,36 | | | 1000 | | |
| CNN 9,12,18,25 | | | 998 | | |
| CNN 32,40,50,60 | | | 1051 | | |
| CNN 70,80,90 | | | 1527 | | |
| TK 25, 35, 65 | | | 998 | | |
| CNB 9, 21, 31, 12 | | | | 1854 | |
| CNB 16, 22, 30 | | | | 1944 | |

Napomena: - Kod izvedbi "pojačanih" kompleta glavnih kontakata, gore navedene cene se povećavaju za 30%
 - Cene kalema se odnose samo na standardne napone upravljanja
 - Za nestandardne napone cena je 10% veća

| Pomoćni kontakti za UTKN | RSD |
|--------------------------|------|
| CN 10/16 | 830 |
| CN 25/40 | 895 |
| CNM 36-110 | 4761 |
| CN 63-250 | 4898 |